

Description

This tape consists of a white, closed-cell polyethylene foam coated on both sides with a modified polyacrylate adhesive. This modified acrylate adhesive possesses a high initial adhesion, even on rough and difficult substrates.

Release paper

blue paper, both sides coated with silicone

Adhesive

modified acrylate

Area of use

For the installation of spray cast and extruded plastic parts such as panels, bars and ducts, as well as plexiglass mirrors for interior fit-outs and displays. For use as an adhesive medium for hooks, signs, handles and dispensers. Ideal for use in exhibition and conference fit-outs.

Technical data

Thickness* (PE foam and adhesive)	1150 micron
Density* (PE-Foam)	67 kg/m ³
Temperature resistance	-40°C to +80°C
Adhesive power*	min. 18 N/25 after 24h min. 18 N/25 after 20min 18 N/25mm after 1min
Shear strength*	min. 300h at 23°C min. 6h at 70°C
Shelf life	2 years
Application temperature	min. 15°C

* average ** in original packaging, at 20°C and 50% relative humidity

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORAFOL Klebtechnik GmbH - Am Biotop 2 - D 16515 Oranienburg
Telefon: +49 (0) 33 01/864 0 - Telefax: +49 (0) 33 01/864 100
E-Mail: verkauf@orafol.de - Internet: <http://www.orafol.de>